



• Intelligent

• High Accuracy

• Dual-Use

FV-2009T

LCDT®

www.Lcndt.net

FV-2009T Intelligent LED Industry X-ray Film Viewer

Characteristic:

Portable LED film viewer combine with Densitometer
 High Luminance: $\geq 120,000 \text{ Cd/m}^2$
 Density: $\geq 4.1\text{H/D}$
 Viewing Screen: 8' X 2.5' (200 X 60mm)
 High Accuracy: $\pm 0.02\text{D}$
 Program Mode for customer calibration(patent technology)
 Separated design, easy for maintainence
 Rugged design, whole alloy aluminium

Specification:

Uniformity : $g \geq 0.95$	Diffusion : $\sigma' \geq 0.95$
POWER:85~264VAC 47~63Hz (Full range)	
Rated Power: 50W	Weight:5.5lb
Dimension: 18' X 5.5' X 2.5' (LxWxH)	

Manufacturer of NDT equipments

WenZhou LuCheng NDT Equipment Corp.

RM.308,Kang Yuan South Building XinCheng Road,
325000 WenZhou, P.R.China.

Tel.:0086-577-88293040

Fax:0086-577-88259689

Web:www.Lcndt.net

E-mail:Lcndt@163.com



www.lcndt.net

We can do better



ISO9001 Registered

PRODUCT CERTIFICATE

PRODUCT Industrial LED Film Viewer

MODEL FV-2009T

SERIAL NO. 0901574

MEASUREMENT BASED ON EN25580 / ISO5580 / ASTM 1790-90

MEASUREMENT RESULT QC Passed



Testing Report:

Maximum Luminance: 120,000Cd/m² Uniformity g: 0.95

Diffusion factor σ' : 0.95 Maximum Reading Density: 4.1H/D

Film Density	ASTM/EN/ISO MIN. Cd/m ²	TEST MAX. Cd/m ²
2.21	30	583.2
3.17	10	80.4
3.66	10	25.5
4.29	10	6.88

NOTE: The luminance mentioned in above table is measured light through the film.

Calibration Report:

AGFA Density Strip (SN.: <u>1001311</u>)								
Num.	0	1	2	3	4	5	6	7
Density:	0.15	0.30	0.60	0.90	1.21	1.50	1.80	2.10
Cal.:	0.16	0.30	0.59	0.91	1.21	1.50	1.79	2.11
AGFA Density Strip								
Num.	8	9	10	11	12	13	14	
Density:	2.41	2.69	2.98	3.26	3.59	3.91	4.21	
Cal.:	2.41	2.70	2.98	3.25	3.58	3.91	4.22	

INSPECTOR INSPECTOR 3 MANAGER INSPECTOR 1 Date: 2013.9.1

Lu Cheng NDT Equipment Corp.

E-mail: Sales@Lcndt.net (For sales) gm@Lcndt.net (For service)

Http://www.Lcndt.net Phone: 86-577-88293040 Fax: 86-577-88259689