

Drive

1-4 Axis Motor Controller



Drive is an 'all-in-one' scanner controller, capable of manipulating one to four motorised axes simultaneously in a precisely controlled and coordinated manner.

Using Linear Amplifiers, rather than noisy pulse width modulation, Drive can produce 150W of motor power, with minimal interference to UT, TOFD, PA and EC signals, enhancing inspection quality and reducing inspection time.

Benefits

- Linear amplifiers provide 150W of motor power across all axes, for interference-free NDT signals
- Fully contained computer and control system, eliminating the need for extra equipment and easier site access
- Remote control via Ethernet or consumer joypad/ joysticks. Can be left on sensitive inspection sites without an on-site inspections engineer
- Fully customisable, built-in automated scan plans, reducing set-up times
- Flexible GPIO interface permits synchronised control over other equipment e.g. pneumatics, sensors and cameras, offering a single control interface
- Industry-standard military grade connector ensuring compatibility with existing scanning devices
- Rugged, site ready construction

Equipped with a powerful Windows 10 integrated touchscreen PC for control, Drive has built-in automated scan plans which are fully customisable. A flexible GPIO interface permits synchronised control over other equipment such as pneumatics, sensors and cameras.

Drive has a familiar "umbilical" connector that makes it simple to connect to existing scanning equipment and has the added advantage of remote control via Ethernet, so can remain in-situ on sensitive inspection sites without an on-site inspection engineer.

Whilst Drive performs best with Phoenix ISL scanning solutions, it provides general purpose and customisable control software to work with any scanner up to 4-axes of movement.

Drive Capabilities

- **Motors**
 - 1 to 4 Brushed DC motors
 - 2A Continuous, 6A Peak
 - Max output 150W across all axes
 - Brake, 24V, 250mA
- **Encoders**
 - 5V, Single, Differential, Index, 20MHz
 - Isolated output to instrumentation
- **Limits**
 - 24V, Forward, Backward, Home
 - NPN/PNP, NO/NC

General Purpose IO port

- Used for peripheral hardware
- Pneumatics, Sensors, Actuators
- 5x 5V Digital Inputs and Outputs
- 5V, 12V, 24V supplies

Integrated touch screen PC

- Fully contained computer and control system
- Export profiles to USB
- Upgrade software via USB
- Fully licensed Microsoft Windows 10
- Fast start-up times
- Uses consumer USB joypad/joysticks
- Remotely accessible

Safety Features

- On-board emergency stop
- Compulsory remote emergency stop

International Power Supply

- 90-250VAC
- 50-60Hz

Weight & Dimensions

- 485x392x192mm
- 12Kg

Compatible Phoenix Solutions

Automated and custom-design scanning solutions including:



Maxi-SAGE Solutions



TSIS System



PET - Pipe Elbow Tracker

Kit

- Drive Motor Controller
- Housed in rugged hand-carry case
- Remote emergency stop



Order Information

Order Code	Description
AE-DRV-L2	2 axis - Low Power (6A/motor) 150W
AE-DRV-L4	4 axis - Low Power (6A/motor) 150W
AE-DRV-H2	2 axis - High Power (10A/motor) 500W

Phoenix Inspection Systems Limited, Dalton House, 40 Hardwick Grange, Warrington, WA1 4RF, United Kingdom

t: +44 (0) 1925 826000 | f: +44 (0) 1925 838788 | e: sales@phoenixisl.com | www.phoenixisl.com

Phoenix Inspection Systems Limited is a Nova Instruments company. For further information visit www.novaic.com

Phoenix Inspection Systems Limited has a policy of continuous development therefore reserves the right to change products, specifications and pricing without forward notice. Actual products may differ from those presented herein. The information in this datasheet is accurate at time of publication.